



## 590.EM4015

### SWITCH DISCONNECTOR

40A 3P+N IP66/IP69 110x150x87mm Y1  
EMERGENCY YELLOW/RED GW 650°C IK09

Product Approvals

| TECHDATA                |                     | STANDARDS AND LAWS                |   |
|-------------------------|---------------------|-----------------------------------|---|
| Commercial series       | ISOLATORS-TP Series | EN 60947-3 (2009)                 | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Type of product         | SWITCH DISCONNECTOR | EN 60947-1 (2007)                 | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules  |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1/A1 (2011)              | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules  |
| Material                | ENGINEERING PLASTIC | EN 60947-3/A1 (2012)              | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units   |
| Protection degree IP    | IP66/IP69           | EN 60947-1/A2 (2014)              | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules  |
| Type                    | EMERGENCY           | EN 60947-3/A2 (2015)              | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units   |
| Colour                  | YELLOW/RED          | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Rated current           | 40A                 |                                   |   |
| Poles                   | 3P+N                |                                   |   |
| Switch size             | Y1                  |                                   |   |
| Rated voltage           | 690V                |                                   |   |
| Dimensions              | 110x150x87mm        |                                   |   |
| GLOW WIRE               | GW 650°C            |                                   |   |
| Protection degree IK    | IK09                |                                   |   |
| Flange                  | 106X150MM           |                                   |   |